

# Expo Brush Coat (Cement Paint)



## **DESCRIPTION**

### **USE:**

Expo Brush Coat is a cementitious product formulated for application as a cement paint to color stucco and masonry surfaces. The product may be used to even the color of new work or refresh stucco in service.

### **COVERAGE:**

A two-coat application (generally required) of Expo Brush Coat will require approximately one pound of product for each square yard.

### **COMPOSITION:**

Expo Brush Coat is mechanically blended formulation of portland cement, hydrated lime, mineral oxide pigments and other additives. Expo Brush Coat is generally sold in 25 pound sacks.

### **ADVANTAGES:**

Expo Brush Coat is milled in special machinery to achieve the high degree of fineness that insures excellent dispersion of pigment and cementitious material in solution.

### **COLOR:**

Expo Brush Coat can be produced to match most Expo Exterior Stucco colors.

### **SHELF LIFE:**

Six (6) months if kept in dry condition.

## **JOB PROCEDURE**

### **SUBSTRATE:**

Clean wall of all foreign matter and patch cracks or breaks at least one day before beginning brush coat application.

Note: Do not apply over painted or sealed surfaces.

### **MIXING:**

Add clean water slowly to powder and stir until a smooth, thick paste is formed. Allow to sit 10 to 15 minutes before adding additional water to obtain a smooth mixture about the consistency of thin paint. It is critical that all batches on the same job have the same proportion of water to powder.

### **APPLICATION:**

Spray wall lightly and evenly with water 30 minutes before applying Expo Brush Coat with a large brush (usually a six-inch cold water paint brush). Complete walls to a break, do not joint.

Note: Brush Coat is not recommended for use as a finish coat over scratch and brown.

### **MATERIAL STANDARDS:**

Hydrated Lime: Federal Specification SS-L-351B, Type F and Type M, A.S.T.M. Designations C206-84 (Type S) and C207-79 (Type S), U.B.C. Standard No. 24-18-82.

Portland Cement: Type 1 A.S.T.M. Designation C150-56, Federal Specification SS-C-192 B.

Expo Stucco, 7455 Carroll Road, San Diego, CA 92121-2379, (858) 566-3110

[www.expostucco.com](http://www.expostucco.com)