

Expo Interior Fastpatch



DESCRIPTION

USE:

Designed for use as a quick-setting one-coat application to match existing interior plaster.

COVERAGE:

One 25-pound bag will cover approximately 12 square feet at a thickness of 1/2-inch. Coverage will vary with thickness applied.

COMPOSITION:

Expo Interior Fast Patch is a mechanically blended compound of gypsum-based plaster, hydrated lime, inert aggregates and other additives, packed in sealed, water-resistant multi-wall bags.

ADVANTAGES:

Expo Interior Fast Patch will set hard in less than one hour and under moderate atmospheric conditions, can be painted in 7 days.

SHELF LIFE:

Six (6) months if kept in dry condition.

JOB PROCEDURE

SUBSTRATE:

Surface should be clean and free of loose material, oil and dirt.

MIXING:

Use approximately 2 gallons of clean water to 25 pounds of product. Mix thoroughly to a uniform, thick consistency.

APPLICATION:

Apply all mixed material within 15 to 20 minutes. Apply with trowel, forcing patch into cracks and crevices to insure good bonding. Level patch using a straight edge. After initial set, water trowel slightly, allow patch to set, then trowel smooth.

NOTE:

Expo Interior Fast Patch should not be retempered.

MATERIAL STANDARDS:

Hydrated Lime: Federal Specification SS-L-351B, Type F and Type M, A.S.T.M.

Designations C206-84 (Type S), and C207-79 (Type S), U.B.C. Standard NO. 24-18-82.

Regular Keenes Cement Federal Specification SS-C161A Type 1, A.S.T.M. Designation C61.