



Expo Plaster-Bond

PVA Plaster Adhesive

DESCRIPTION:

Expo Plaster-Bond is a multi-purpose, re-emulsifiable, liquid polyvinyl acetate homopolymer bonding agent. It provides excellent adhesion to a wide variety of porous and non-porous substrates. Expo Plaster-Bond allows stucco and plaster mixes to bond to existing Portland cement surfaces.

USE:

Expo Plaster-Bond is excellent for use as a bonding agent for stucco color coat, plaster mixes and concrete mortars.

COVERAGE:

When used as a bonding agent, Expo Plaster-Bond will cover approximately 200 to 300 square feet per gallon.

APPLICATION TECHNIQUE:

Plaster-Bond may be applied by roller, brush, or sprayer.

ADVANTAGES:

- Does not require any mixing
- Improves adhesion to a variety of substrates
- Simple to use
- High resistance to efflorescence
- May be used with gypsum plasters
- Non-flammable, VOC compliant
- Economical

PACKAGING AND STORAGE:

Expo Plaster-Bond is available in 1 gallon plastic bottles, 5 gallon plastic pails and 55 gallon drums. Store in protected areas where ambient temperature is between 40 and 100 degrees F.

SHELF LIFE:

When properly stored, 1 year in unopened, original container.

COLOR:

Pink

SURFACE PREPARATION:

Take care that the surface is structurally sound, clean and free of dust, silicones, efflorescence or other contaminants. If the receiving surface is questionable, please contact your Expo Stucco Products sales representative.

MIXING:

Expo Plaster-Bond is ready-to-use.

APPLICATION:

Expo Plaster-Bond is applied by brush, roller or sprayer. Allow Plaster-Bond to dry before application of wet plaster materials or cement mixes. New plasters and cement mixes should be applied within 72 hours of applying Plaster-Bond.

LIMITATIONS:

Do not apply to frost-covered or frozen surfaces, below-grade surfaces, surfaces which are exposed to hydrostatic pressure or exterior horizontal surfaces. Do not use when the ambient temperature is 40 degrees F or below. Proper application is the responsibility of the applicator. Continual exposure to moisture may cause re-emulsification.

CLEAN-UP:

With water, clean all tools immediately after use. Cover all surrounding areas which may be subject to oversprays or spills.

CAUTIONS:

Expo Plaster-Bond may be irritating to skin. Wear appropriate safety equipment during use i.e., small particle dust mask, safety goggles. In case of eye contact, flush eyes immediately with clean water and see a physician. Wash hands and skin with soap and hot water after using. Do not take internally. KEEP AWAY FROM CHILDREN. Consult Material Safety Data Sheet for further information.